Motorised swing gate turnstile

Elegant quality.

Harmonious, elegant, silent and guick

Wing features numerous qualities! It fits perfectly in even the most prestigious settings such as hotels, business facilities, casinos, showrooms, and fitness/ wellness centres. It is designed to ease passage for physically challenged people.







Flow management. To better manage flows you can integrate Wing with the modular post and rail system.

only authorised personnel to restricted areas



Perfect integration. Opens via command device. and can be integrated with Came's access control systems. It allows you to clear



24V only


Its 24V power rating makes for easier installation and also guarantees enhanced safety for users.



Advantages of Wing

Wing is the bidirectional, motorised swing gate, featuring an AISI 304 Inox steel structure with IROKO wooden cover - and a 10 mm thick, transparent, polycarbonate swing-leaf. It's extremely versatile in that the leaf's design may be customised to your liking, while the materials used to make it suitable for every situation. Wing is fitted with a timed closure and a push-to-open antipanic system. For those wider passage ways. It's also available in double configuration, employable at wider passage ways.

Dimensions





Technical featu	res			
Туре	PSEPCSS00	PSEPCSD00	PSEPCSS00CT	PSEPCSD00CT
Power supply (V) (50/60Hz)	24V D.C.	24V D.C.	24V D.C.	24V D.C.
Protection rating (IP)	40	40	40	40
Current draw (A)	2,5	2,5	2,5	2,5
Weight (Kg/lb)	40 / 88	40 / 88	40 / 88	40 / 88
Operating temperature (°C/°F)	-20 ÷ +55 / -4 ÷ +131	-20 ÷ +55 / -4 ÷ +131	-20 ÷ +55 / -4 ÷ +131	-20 ÷ +55 / -4 ÷ +131
120V A.C 60 Hz PRODUCTS, PLEASE CHECK OUR PRICE LIST				24V D.C



The complete range

Motorised swing-leaf gate

- Parking systems and access control price list -

001 PSEPCSS00	24V D.C. motorised, bidirectional swing-leaf gate complete with control board and
	push-to-open antipanic system. Plexiglass swing-leaf.



001PSEPCSD00 24V D.C. motorised, bidirectional double swing-leaf gate complete with control board and push-to-open antipanic system. Plexiglass finish swing-leaf.

001PSEPCSS00CT 24V D.C. motorised, bidirectional single swing-leaf gate complete with control board and push-to-open antipanic system. Tempered glass finish swing-leaf.

001PSEPCSD00CT 24V D.C. motorised, bidirectional double swing-leaf gate complete with control board and push-to-open antipanic system. Tempered glass finish swing-leaf.

Additional accessories



001PSCSCR04 Remote control console for up to 4 through-ways.

Complementary accessories



001PSOPAL01 24V D.C., 2.5A switching feeder, complete with IP65 class casing for one turnstile 001**PSOPAL06** 24V D.C., 6.5A switching feeder, complete with IP65 class casing for two turnstiles.



001PSOPEPCDIS Gate leaf for the physically challenged. Leaf width: 900 mm

001PSOPEPCDISCT Tempered glass gate leaf for the physically challenged. Leaf width: 900 mm

To couple with access control systems see RBM84 on p. 208



